

Product Features

- High Definition AHD 5.0 Megapixel Sensor (5510+FH8538M)
- 42PCS IR LED, 40Meter IR Distance
- 2.8~12mm varifocal MP lens
- HD AHD video output, no delay, lossless, long distance transmission
- Reach 500 meters coaxial cable real-time transmission
- Support low illumination, auto color to black
- Support ICR switch, realize day & night monitor
- Support 3D noise reduction
- Metal Case Bullet camera with 3-axis bracket, hidden IR LED



AHD 5MP Series IR Waterproof Camera **QH8531B**

Specification	
Model	QH8531B
System	PAL/NTSC
Solution	1/3" 5510+FH8538M
Effective Pixels	2592*1944
Video output	1.0Vp-p, 75Ω Composite, BNC x 1
Horizontal resolution	5MP
S/N Ratio	>52dB (AGC OFF/BW OFF)
illumination	0.001 Lux
Minimum illumination	0.0001 Lux(IR ON)
Electronic Shutter	1/50 - 1/10,000S
White Balance	Auto
Gamma Ratio	≥0.45
Color of camera housing	white
Infrared	42PCS IR LED
IR Distance	40Meter IR Distance
Infrared Wavelength	850nm
Waterproof	IP66
Lens Mount	2.8~12mm MP lens
Operating Temperature	Outdoor: -10C to 50C
Humidity	0 to 95% RH (non-condensing)
Sync system	2:1 interlace internal Sync.
Power supply	12V DC